ND SOFTWARE LIBRARY DISKETTE

PAGE 1

Containing : RP for ND-100

(English version)

Directory Name : 211065C02-EN-010

User Name : FLOPPY-USER

	# / 9 v	Type	т	File at	ccess: Friend	0wn	Pages	Bytes
Nr	File name	Type	·.	, , , , , , ,				
0	INST-RP-100-C02	PROG	I	RWACD	RWASD	RHACD	6 4	184258
•	RP-SETUP-CO2	XCOM	1.	RWACD	RWALD	PHACD	6	8222
2	NOTIS-RPO-EN-CO2	PROG		RWACD	RWAGD	RWACD	80	397312
3	NOTIS-RP1-EN-C02	PROG		RWACD	RWAGO	RHACD	72	399360
4	UE-ERMSG-EN-BO3	ERR	Ĩ	RWACD	Of the buston	RWACD	46	90880
5	files using 268	<u>ರಾವ</u> ಭಾಕತ		enn pag	es . 433 은	rved out	of 610	pages.

Date 86.11.		Data A/S DESCRIPTION	Page	1 of 5
Product	Name RP for ND-100		Reg. no. 211065C	Category STPR
Reason	* New product Change/Addition		ror Correct fferent Env	
Documen- tation	Title NOTIS-RG Reference NOTIS-RG Referanset			Reg. no. 63.013.5 EN 63.014.5 NO
Purpose	General purpose rep	ort generator	- runtime	part.
Prerequi- sites	Computer Type Flo ND-100 48	oating format or 32 bit	Op. syste SIN III V	
	SYSTEM 21	serspace 95 pages on	Number of	tion files
	SYSTEM	mass storage r serspace O pages or 51 pages or	Number of 0 files	files
	Max/Min number of Max/Min number of Space requirements	segments:	Max 2	Min 2
Product consists of	MODULE-no. Name		Reg. no	o. for Source
* <rev> = File no. F 209003C I 209004C R</rev>	NST-RP-100-C	N-01S User Na Type PROG XCOM PROG	Containing Installation Inst. Util Main segme	on Program ities
Directory	Name: 211065C <rev>-E</rev>	N-02S User N	ame: FLOPPY	-USER
	ile Name OTIS-RP1-EN-C E-ERMSG-EN-B03	Type PROG ERR	Containing Sub segmen Error mess	t RP (EV)

تر 2

Date 86.1	1.26 Norsk Data PROGRAM DESCRI	· • -	2 of 5
Product	Name	Reg. no.	Category
	RP for ND-100	211065C	STPR

Directory	Name: 211065C <rev>-NC</rev>	1-013	oser			LIN
File no.	File Name	Type			aining	
	INST-RP-100-C	PROG			tallation (
	RP-SETUP-C	XCOM		Inst	t. utiliti	e s
	NOTIS-RPO-NO-C	PROG		Mait	n segment	RP (NV)
					•	
Directory	Name: 211065C <rev>-NO</rev>	0-025	User	Name:	FLOPPY-US	ER
		0-02S Type	User		FLOPPY-US	ER
File no.			User	Con		

(EV) = English Version (NV) = Norwegian Version
* <rev> = current revision

1 ERRORS CORRECTED

===

This is the first version of the NOTIS-RG run-time program, 'NOTIS-RP', as separate product.

2 PREREQUISITES

- To read data from local SIBAS databases, RP version C requires SIBAS version D or later.
- To read from remote SIBAS databases, SIBAS-BACKEND version F must be installed.

Date 86.1	1.26 Norsk Data A/S PROGRAM DESCRIPTION	Page :	of 5
Product	Name	Reg. no.	Category
	RP for ND-100	211065C	STPR

3 INSTALLATION PROCEDURE

التريت

RP for ND-100 is the run-time part of NOTIS-RG report generator. RP is an abbreviation for 'Report Producer'.

The program is installed as reentrant subsystem 'NOTIS-RP', and may be used to produce reports defined with NOTIS-RG version C or older.

RP for ND-100, English version is supplied on two diskettes, with directory names 211065C<rev>-EN-01S and 211065C<rev>-EN-02S. For Norwegian version, the corresponding directory names are 211065C<rev>-NO-01S and 211065C<rev>-NO-02S. If you have ordered DS/DD diskettes, one diskette (211065C<rev>-EN-01D or 211065C<rev>-NO-01D) is supplied.

The procedure to load RP version C is as follows:

- 1) Log in as user SYSTEM.
- 2) Make sure that the required number of pages and files is free on user SYSTEM (prerequisites, page 1).
- 3) RP should always be installed on SINTRAN user NOTIS. This user must have some free pages (see prerequisites, page 1). Make sure that the user exists, and has enough ree pages! NOTE: if you want to install several language versions of RP, the space requirements on user NOTIS will add up.
- 4) Insert the diskette 211065C<rev>-EN-01 in your diskette station (211065C<rev>-NO-01 for Norwegian version).
- 5) Enter this directory by typing <u>DENTER-DIR_FLOPPY-D-1</u>
- 6) Start the installation program by typing a(211065:FLOPPY-USER)INST-RP

The installation program will then guide you through the installation. It asks which language version(s) to install. Your answer must correspond to the diskette set(s) you have. If you have ordered both Norwegian and English version, the installation program should be used to install both language versions at the same time.

You are asked to insert the other diskettes when required.

To check that the installation was successful, you may inspect the file (SYSTEM)RP-100-DUMP-C:LOG. This file is output by the installation MODE job. Delete the file when you have looked at it.

Date 86.11	1.26 Norsk Data A/S PROGRAM DESCRIPTION	Page 4	6 of 5
Product	Name	Reg. no.	Category
	RP for ND-100	211065C	STPR

The installation leaves a temporary file on user SYSTEM, (SYSTEM)INSTALL-RP-C:TEMP. This file should be deleted.

4 RE-INSTALLATION FROM DUMP-REENTRANT FILE

The installation program makes a :MODE file that should later be run to re-install RP. Remember to update the DUMP-REENTRANT (or HENT-MODE) file with this command :

amode (NOTIS) RP-100-DUMP-C: MODE. .

5 THE ERROR MESSAGE FILE

ترت

If you already have a version of the error message file UE-ERMSG-EN-B:ERR, the file UE-ERMSG-EN-B03:ERR will be copied to a file named UE-ERMSG-EN-B03:NEW (on user SYSTEM).

If you want to use this new file, please delete the old file UE-ERMSG-EN-B:ERR, and rename the new file by typing :

DELETE-FILE (SYSTEM)UE-ERMSG-EN-B:ERR → DRENAME-FILE (SYSTEM)UE-ERMSG-EN-BO3:NEW :ERR →

Date 86.1	1.26 Norsk Data A/S PROGRAM DESCRIPTION	Page	5 of 5
Product	Name	Reg. no.	Category
	RP for ND-100	211065C	STPR

6 CHANGE ISAM INTERNAL DEVICE

ترية

The ISAM version loaded with RP is a multiuser ISAM, allowing ISAM files to be accessed in multiuser mode. The ISAM version loaded with NOTIS-RP will by default use internal devices 2008 and 2018.

Internal devices are only used if the ISAM multiuser supervisor (ISAMRT) is installed on your computer. If your ISAM multiuser supervisor uses other device numbers than 2008/2018, you must change the device number in NOTIS-RP. After NOTIS-RG/RP version C is installed, you may change the device numbers this way:

- 1) Log in as user NOTIS.
- 2) Use the program LOOK-FILE to change the device number in the NOTIS-RP program file. Note that ISAM will use the device number entered, and the succeeding device number (as shown below, 2028 and 2038):

DLOOK-FILE
>>OPEN NOTIS-RPO-EN-C:PROG...
>>PATCH 139 42
000052 (42)/000200 : 202B (or an other number)
000053 (43)/025432 : _
>>EXIT

- 3) Log in as user SYSTEM.
- 4) Run the mode file that dumps NOTIS-RG and NOTIS-RP :

amode (NOTIS) RP-100-DUMP-C: MODE.

Date 86.11.		sk Data A/S AM DESCRIPTION	Page	1 of 5
Product	Name RP for ND-100		Reg. no. 211065C	Category STPR
Reason	* New product Change/Addition		ror Correct fferent Env	
Documen- tation	Title NOTIS-RG Referer NOTIS-RG Referar		**	Reg. no. 63.013.5 EN 63.014.5 NO
Purpose	General purpose	report generator	- runtime	part.
Prerequi- sites	Computer Type ND-100	Floating format 48 or 32 bit	Op. syste	m Version 'S I,J,K
	Minimum mass sto User SYSTEM NOTIS	orage resources Userspace 205 pages of 157 pages of	Number of	files
	Minimum permane User SYSTEM NOTIS	nt mass storage : Userspace 0 pages 0 151 pages o	Number of	files
	May/Min number	of RT-descriptio of segments: nts on segment f	Max	2 Min 2
Product consists	MODULE-no. Name		Reg. n	o. for Source
of			2105	77C ·
Directory	Name: 211065C <rev< td=""><td>>-EN-01S User N</td><td>ame: FLOPPY</td><td>-USER</td></rev<>	>-EN-01S User N	ame: FLOPPY	-USER
File no.		Type	Containing	
	INST-RP-100-C	PROG	=	on Program
209004C	RP-SETUP-C	XCOM	Inst. Util	
204421C	NOTIS-RPD-EN-C	PROG	Main segme	ent RP (EV)
Directory	Name: 211065C <rev< td=""><td>/>-EN-02S User h</td><td>lame: FLOPPY</td><td>-USER</td></rev<>	/>-EN-02S User h	lame: FLOPPY	-USER
File no.	File Name	Type	Containing	
204422C	NOTIS-RP1-EN-C	PROG	Sub segmer	
204622B	UE-ERMSG-EN-BO3	ERR	Error mess	sages (EV)

===

Date 86.1	Norsk Data A/S PROGRAM DESCRIPTION	Page 2	2 of 5
Product	Name	Reg. no.	Category
	RP for ND-100	211065C	STPR

Directory	Name: 211065C <rev>-NO-</rev>	-015	User	Name: FLOPPY-USER
	File Name INST-RP-100-C	Type PROG		Contain <u>i</u> ng Installation Progra Inst. utilities
209004C 204497C		XCOM PROG		Main segment RP (NV
Director	y Name: 211065C <rev>-NO</rev>	-025	User	r Name: FLOPPY-USER
	File Name NOTIS-RP1-NO-C	Type PROG		Containing Sub segment RP (NV)
204433C		ERR		Error messages (N

(EV) = English Version (NV) = Norwegian Version * <rev> = current revision

1 ERRORS CORRECTED

ترت

This is the first version of the NOTIS-RG run-time program, 'NOTIS-RP', as separate product.

2 PREREQUISITES

- To read data from local SIBAS databases, RP version C requires SIBAS version D or later.
- To read from remote SIBAS databases, SIBAS-BACKEND version F must be installed.

Date 86.1	1.26 Norsk Data A PROGRAM DESCRIP		of 5
Product	Name	Reg. no.	Category
	RP for ND-100	211065C	STPR

~

3 INSTALLATION PROCEDURE

=2

RP for ND-100 is the run-time part of NOTIS-RG report generator. RP is an abbreviation for 'Report Producer'.

The program is installed as reentrant subsystem 'NOTIS-RP', and may be used to produce reports defined with NOTIS-RG version C or older.

RP for ND-100, English version is supplied on two diskettes, with directory names 211065C<rev>-EN-01S and 211065C<rev>-EN-02S. For Norwegian version, the corresponding directory names are 211065C<rev>-NO-01S and 211065C<rev>-NO-02S. If you have ordered DS/DD diskettes, one diskette (211065C<rev>-EN-01D or 211065C<rev>-NO-01D) is supplied.

The procedure to load RP version C is as follows:

- 1) Log in as user SYSTEM.
- 2) Make sure that the required number of pages and files is free on user SYSTEM (prerequisites, page 1).
- 3) RP should always be installed on SINTRAN user NOTIS. This user must have some free pages (see prerequisites, page 1). Make sure that the user exists, and has enough free pages! NOTE: if you want to install several language versions of RP, the space requirements on user NOTIS will add up.
- 4) Insert the diskette $211065C\langle rev\rangle-EN-01$ in your diskette station ($211065C\langle rev\rangle-N0-01$ for Norwegian version).
- 5) Enter this directory by typing <u>DENTER-DIR., FLOPPY-D-1</u>,
- 6) Start the installation program by typing a(211065:FLOPPY-USER)INST-RP

The installation program will then guide you through the installation. It asks which language version(s) to install. Your answer must correspond to the diskette set(s) you have. If you have ordered both Norwegian and English version, the installation program should be used to install both language versions at the same time.

You are asked to insert the other diskettes when required.

To check that the installation was successful, you may inspect the file (SYSTEM)RP-100-DUMP-C:LOG. This file is output by the installation MODE job. Delete the file when you have looked at it.

Date 86.11.	.26 Norsk Data A/S PROGRAM DESCRIPTION	Page 4	6 of 5
Product	Name	Reg. no.	Category
	RP for ND-100	211065C	STPR

The installation leaves a temporary file on user SYSTEM, (SYSTEM)INSTALL-RP-C:TEMP. This file should be deleted.

4 RE-INSTALLATION FROM DUMP-REENTRANT FILE

The installation program makes a :MODE file that should later be run to re-install RP. Remember to update the DUMP-REENTRANT (or HENT-MODE) file with this command :

amode (NOTIS) RP-100-DUMP-C: MODE ...

5 THE ERROR MESSAGE FILE

=2

If you already have a version of the error message file UE-ERMSG-EN-B:ERR, the file UE-ERMSG-EN-B03:ERR will be copied to a file named UE-ERMSG-EN-B03:NEW (on user SYSTEM).

If you want to use this new file, please delete the old file UE-ERMSG-EN-B:ERR, and rename the new file by typing :

DELETE-FILE (SYSTEM)UE-ERMSG-EN-B:ERR ← SPENAME-FILE (SYSTEM)UE-ERMSG-EN-BO3:NEW :ERR ←

Date 86.1	1.26 Norsk Data A/S PROGRAM DESCRIPTION	Page 5	5 of 5
Product	Name	Reg. no.	Category
	RP for ND-100	211065C	STPR

6 CHANGE ISAM INTERNAL DEVICE

تر ب

The ISAM version loaded with RP is a multiuser ISAM, allowing ISAM files to be accessed in multiuser mode. The ISAM version loaded with NOTIS-RP will by default use internal devices 200B and 201B.

Internal devices are only used if the ISAM multiuser supervisor (ISAMRT) is installed on your computer. If your ISAM multiuser supervisor uses other device numbers than 2008/2018, you must change the device number in NOTIS-RP. After NOTIS-RG/RP version C is installed, you may change the device numbers this way:

- 1) Log in as user NOTIS.
- 2) Use the program LOOK-FILE to change the device number in the NOTIS-RP program file. Note that ISAM will use the device number entered, <u>and</u> the succeeding device number (as shown below, 2028 and 2038):

<u>alook-File</u>
>> <u>OPEN NOTIS-RPO-EN-C:PROG...</u> (-NO- for Norwegian ver.)
>> <u>PATCH 139 42</u>
000052 (42)/000200 : <u>202B</u> (or an other number)
000053 (43)/025432 : ...
>> <u>EXII</u>

- 3) Log in as user SYSTEM.
- 4) Run the mode file that dumps NOTIS-RG and NOTIS-RP :

amode (NOTIS) RP-100-DUMP-C: MODE ...